

Safety Data Sheet

Issue Date: 23-May-2019

Revision Date: 02-Aug-2019

Version 1

1. IDENTIFICATION

Product identifier

Product Name

OHM-SHIELD GP-5600 Grey Floor Paint

To order online: https://store.unitedesd.com/Static_Solutions_GP_5600_s/92.htm

Other means of identification

SDS

STAT-004

Recommended use of the chemical and restrictions on use

Recommended Use

Static Control Paint.

Details of the supplier of the safety data sheet and product

Supplier Address

United SCP

4301 32nd St W.

Suite B-20

Bradenton, FL 34205

Phone: 719 676 3928

Emergency telephone number

Emergency Telephone

INFOTRAC 1-352-323-3500 (International)

1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Classification

Reproductive toxicity

Category 1B

Signal Word

Danger

Hazard statements

May damage fertility or the unborn child



Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other hazards

Harmful to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No	Weight-%
Titanium(IV) Oxide	13463-67-7	10-15
Ethylene glycol monopropyl ether	2807-30-9	<5
Diethylene Glycol Monobutyl Ether	112-34-5	<5
Butyl benzyl phthalate	85-68-7	<5
Carbon Black	1333-86-4	<5
N-methyl-2-pyrrolidone	872-50-4	<1

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

- General Advice** If exposed or concerned: Get medical advice/attention.
- Eye Contact** Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids. Consult a physician.
- Skin Contact** Wash off immediately with plenty of water for at least 15 minutes.
- Inhalation** Remove to fresh air.
- Ingestion** Clean mouth with water and drink afterwards plenty of water.

Most important symptoms and effects, both acute and delayed

- Symptoms** May damage fertility or the unborn child.

Indication of any immediate medical attention and special treatment needed

- Notes to Physician** Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

- Unsuitable Extinguishing Media** Not determined.

Specific Hazards Arising from the Chemical

Not determined.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- Personal Precautions** Use personal protective equipment as required.

Environmental precautions

Methods and material for containment and cleaning up

Methods for Containment Prevent further leakage or spillage if safe to do so.

Methods for Clean-Up Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/protective clothing and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up.

Incompatible Materials None known based on information supplied.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Titanium(IV) Oxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³ TWA: 2.4 mg/m ³ CIB 63 fine TWA: 0.3 mg/m ³ CIB 63 ultrafine, including engineered nanoscale
Diethylene Glycol Monobutyl Ether 112-34-5	TWA: 10 ppm inhalable fraction and vapor	-	-
Carbon Black 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits.

Individual protection measures, such as personal protective equipment

Eye/Face Protection Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin and Body Protection Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory Protection Refer to 29 CFR 1910.134 for respiratory protection requirements.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Not determined	Odor	Not determined
Appearance	Not determined	Odor Threshold	Not determined
Color	Not determined		

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	Not determined	
Melting point / freezing point	Not determined	
Boiling point / boiling range	Not determined	
Flash point	Not determined	
Evaporation Rate	Not determined	
Flammability (Solid, Gas)	Not determined	
Flammability Limit in Air		
Upper flammability or explosive limits	Not determined	
Lower flammability or explosive limits	Not determined	
Vapor Pressure	Not determined	
Vapor Density	Not determined	
Relative Density	Not determined	
Water Solubility	Not determined	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition temperature	Not determined	
Decomposition temperature	Not determined	
Kinematic viscosity	Not determined	
Dynamic Viscosity	Not determined	
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to Avoid

Keep out of reach of children.

Incompatible materials

None known based on information supplied.

Hazardous decomposition products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Avoid contact with eyes.

Skin Contact Avoid contact with skin.

Inhalation Do not inhale.

Ingestion Do not ingest.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Titanium(IV) Oxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Ethylene glycol monopropyl ether 2807-30-9	= 3089 mg/kg (Rat)	= 870 mg/kg (Rabbit) = 960 µL/kg (Rabbit)	= 1530 ppm (Rat) 7 h
Diethylene Glycol Monobutyl Ether 112-34-5	= 5660 mg/kg (Rat)	= 2700 mg/kg (Rabbit)	-
Butyl benzyl phthalate 85-68-7	= 2330 mg/kg (Rat)	= 6700 mg/kg (Rat)	> 6.7 mg/L (Rat) 4 h
Carbon Black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
Sodium Lignosulfonate 8061-51-6	> 40 g/kg (Rat)	-	-
N-methyl-2-pyrrolidone 872-50-4	= 3914 mg/kg (Rat)	= 8 g/kg (Rabbit)	> 5.1 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Titanium dioxide is a possible carcinogen when it appears as a respirable dust. Carbon black is a possible carcinogen when it appears as a respirable dust.

Chemical name	ACGIH	IARC	NTP	OSHA
Titanium(IV) Oxide 13463-67-7		Group 2B		X
Butyl benzyl phthalate 85-68-7		Group 3		
Carbon Black 1333-86-4	A3	Group 2B		X

Legend

- ACGIH (American Conference of Governmental Industrial Hygienists)
- A3 - Animal Carcinogen
- IARC (International Agency for Research on Cancer)
- Group 2B - Possibly Carcinogenic to Humans
- Group 3 IARC components are "not classifiable as human carcinogens"
- OSHA (Occupational Safety and Health Administration of the US Department of Labor)
- X - Present

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

- Oral LD50 25,307.80 mg/kg
- Dermal LD50 15,709.50 mg/kg
- Gas 37,582.80 mg/L
- ATEmix (inhalation-dust/mist) 360.08 mg/L

12. ECOLOGICAL INFORMATION

Ecotoxicity

Harmful to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Diethylene Glycol Monobutyl Ether 112-34-5	100: 96 h Desmodesmus subspicatus mg/L EC50	1300: 96 h Lepomis macrochirus mg/L LC50 static	100: 48 h Daphnia magna mg/L EC50 2850: 24 h Daphnia magna mg/L EC50
Butyl benzyl phthalate 85-68-7	0.02 - 0.25: 96 h Pseudokirchneriella subcapitata mg/L EC50 0.2 - 28.2: 72 h Pseudokirchneriella subcapitata mg/L EC50	0.82: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 1.0 - 10.0: 96 h Oncorhynchus mykiss mg/L LC50 static 0.78: 96 h Pimephales promelas mg/L LC50 static 1.39 - 3.88: 96 h Pimephales promelas mg/L LC50 flow-through 1.0 - 10.0: 96 h Lepomis macrochirus mg/L LC50 static	0.9 - 1.1: 48 h Daphnia magna mg/L EC50 Static 1.28: 48 h Daphnia magna mg/L EC50 semi-static 0.97: 48 h Daphnia magna mg/L EC50 0.76: 48 h Daphnia magna mg/L EC50 Flow through
Carbon Black 1333-86-4			5600: 24 h Daphnia magna mg/L EC50
Sodium Lignosulfonate 8061-51-6		7300: 48 h Oncorhynchus mykiss mg/L LC50	
N-methyl-2-pyrrolidone 872-50-4	500: 72 h Desmodesmus subspicatus mg/L EC50	1072: 96 h Pimephales promelas mg/L LC50 static 832: 96 h Lepomis macrochirus mg/L LC50 static 1400: 96 h Poecilia reticulata mg/L LC50 static 4000: 96 h Leuciscus idus mg/L LC50 static	4897: 48 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

There is no data for this product.

Mobility

Chemical name	Partition coefficient
Butyl benzyl phthalate 85-68-7	3.57 - 4.91
N-methyl-2-pyrrolidone 872-50-4	-0.46

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

- Disposal of Wastes** Disposal should be in accordance with applicable regional, national and local laws and regulations.
- Contaminated Packaging** Disposal should be in accordance with applicable regional, national and local laws and regulations.

14. TRANSPORT INFORMATION

- Note** Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
- DOT** Not regulated
- IATA** Not regulated
- IMDG** Not regulated

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Titanium(IV) Oxide	X	ACTIVE	X	X	X	X	X	X	X
Ethylene glycol monopropyl ether	X	ACTIVE	X	X	X	X	X	X	X
Diethylene Glycol Monobutyl Ether	X	ACTIVE	X	X	X	X	X	X	X
Butyl benzyl phthalate	X	ACTIVE	X	X	X	X	X	X	X
Carbon Black	X	ACTIVE	X	X	X	X	X	X	X
Sodium Lignosulfonate	X	ACTIVE	X		X	X	X	X	X
N-methyl-2-pyrrolidone	X	ACTIVE	X	X	X	X	X	X	X

Legend:

- TSCA - United States Toxic Substances Control Act Section 8(b) Inventory*
- DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List*
- EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*
- ENCS - Japan Existing and New Chemical Substances*
- IECSC - China Inventory of Existing Chemical Substances*
- KECL - Korean Existing and Evaluated Chemical Substances*
- PICCS - Philippines Inventory of Chemicals and Chemical Substances*
- AICS - Australian Inventory of Chemical Substances*

SARA 313

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
Ethylene glycol monopropyl ether - 2807-30-9	2807-30-9	<5	1.0
Diethylene Glycol Monobutyl Ether - 112-34-5	112-34-5	<5	1.0
N-methyl-2-pyrrolidone - 872-50-4	872-50-4	<1	1.0

CWA (Clean Water Act)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl benzyl phthalate		X	X	

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Titanium(IV) Oxide - 13463-67-7	Carcinogen
Butyl benzyl phthalate - 85-68-7	Developmental
Carbon Black - 1333-86-4	Carcinogen
N-methyl-2-pyrrolidone - 872-50-4	Developmental

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Titanium(IV) Oxide 13463-67-7	X	X	X
Ethylene glycol monopropyl ether 2807-30-9	X		X
Diethylene Glycol Monobutyl Ether 112-34-5	X		X
Butyl benzyl phthalate 85-68-7	X	X	X
Carbon Black 1333-86-4	X	X	X
N-methyl-2-pyrrolidone 872-50-4	X	X	X

16. OTHER INFORMATION

NFPA	Health Hazards	Flammability	Instability	Special Hazards
	Not determined	Not determined	Not determined	Not determined
HMIS	Health Hazards	Flammability	Physical hazards	Personal Protection
	Not determined	Not determined	Not determined	Not determined

Issue Date: 23-May-2019
 Revision Date: 02-Aug-2019
 Revision Note: Composition update-KK

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet