

SECTION I - PRODUCT AND COMPANY IDENTIFICATION

Name of the Product (s):
ElectraShield-7077 / UltraSpray II
Product Code: E-Shield / UltraSpray
Product Use: Anti-Static Coating for Carpet
Cloth and Plastics.
Producer:
 United Static Control Products
 4301 32nd Street West, B-21
 Bradenton, FL 34205
Telephone Number for Information: (719) 676-3928
Emergency Phone Number: Local Poison Control Center

SECTION II – HAZARD(s) IDENTIFICATION

Classification:
While this material is not considered hazardous per OSHA Hazard Communication Standard (29 CFR 1910.1200), this SDS contains valuable information that is critical to the safe handling and proper use of the product. The SDS should be retained and available for employees and other users of this product.

Not dangerous according to the Globally Harmonized System (GHS).

Pictogram: Not applicable.
Signal Word: Not applicable.
Hazard Statement: No known significant effects or critical hazards are associated with this material.

Precautionary Statements:
 Keep container tightly closed when not in use.
 No smoking.
 Wear protective gloves and eye/face protection.
 Avoid contact with skin, eyes or clothing.
 Store the material in a cool well-ventilated area.
 Avoid release to the environment.

SECTION III – Composition/Information on Ingredients

Component	CAS#	Weight (%)
Dipropylene glycol monomethyl ether	34590-94-8	1 - 3

SECTION IV – FIRST AID MEASURES

Skin Contact: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes. Get medical attention if irritation develops or persists. Wash contaminated clothing before reuse.

Eye Contact: Move individual away from exposure. Immediately flush eyes with large quantities of clean water for at least 15 minutes. Get immediate medical attention.

Ingestion: DO NOT INDUCE VOMITING. This material may enter the lungs during vomiting. Never give anything by mouth to an unconscious person. GET IMMEDIATE MEDICAL ATTENTION.

Inhalation: If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet. GET IMMEDIATE MEDICAL ATTENTION.

SECTION V – FIRE FIGHTING MEASURES

Suitable Extinguishing Media: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Hazardous Combustion Products: None known.

Fire/Explosion Hazard: None known.

Protective Equipment & Precautions for Firefighters: Wear self-contained breathing apparatus (SCBA) and full fire-fighting protective clothing. Thoroughly decontaminate all protective equipment after use. Evacuate all persons from the fire area to a safe location. Move non-burning material, as feasible, to a safe location as soon as possible. Use water spray to cool fire-exposed containers.

SECTION VI – ACCIDENTAL RELEASE MEASURES

Personal Precautions: Depending on the extent of release, consider the need for fire fighters/emergency responders with adequate personal protective equipment for cleaning up. Do not eat, drink or smoke while cleaning up. Use a self-contained respirator, a mask with filter or a filtering mask. Wear protective clothing, safety glasses and impervious gloves (e.g. neoprene gloves). Ensure adequate ventilation. Avoid all sources of ignition: hot surfaces and open flames (see also section 7).

Environmental Precautions: Prevent spills from entering storm sewers or drains and contact with soil.

Methods for Cleaning Up:

Small Spill: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up. Dispose of via a licensed waste disposal contractor.

Large Spill: Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or other confined areas. Contain and collect spillage with absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazards as the spilled product. Note, see section 1 for emergency contact information and section 13 for waste disposal.

SECTION VII – HANDLING AND STORAGE

Precautions for Safe Handling: Put on appropriate personal protective equipment. Do not get in eyes, skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container, tightly closed, when not in use. Keep away from acids. Empty containers retain product residue and can be dangerous. Do not reuse container.

Advice on General Occupational Hygiene: Eating, drinking and smoking should be prohibited in areas where this product is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also section 8 for additional hygiene measures.

KEEP OUT OF REACH OF CHILDREN

SECTION VIII – EXPOSURE CONTROLS AND PERSONAL PROTECTION

Dipropylene glycol momomethyl ether 34590-94-8

OSHA Z1	permissible exposure limit	600 mg/m ³
ACGIH	time weighted average	100 ppm
ACGIH	short term exposure limit	150 ppm

Appropriate Engineering Controls: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental Exposure Controls: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Exposure Controls: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure levels below TLV(s).

Individual Protection Measures:

Hygiene Measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/Face Protection: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Hand Protection: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.

8 hours (breakthrough time): butyl rubber

Body Protection: Personal protective equipment for the body should be selected based on the task performed and the risks involved. Any and all personal protective equipment should be approved by a specialist before handling this product.

Other Skin Protection: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: natural rubber (latex)

SECTION IX – PHYSICAL PROPERTIES

Appearance	Milky
Odor	Detergent
Odor Threshold	Not available
Physical State	Liquid
pH	5.5 - 6.5
Flash Point (TCC)	Not applicable. Product does not sustain combustion.
Flammability (solid, gas)	Not available
Lower and Upper Explosive Limits	Not available
Vapor Pressure	17.8 mmHg
Vapor Density	1.02
Relative Density	1.02
Solubility	Water soluble
Partition coefficient:	Not available
Auto-Ignition Temperature	Not available
Decomposition Temperature	Not available
Viscosity	5 - 15 cps. @ 25°C

SECTION X – STABILITY AND REACTIVITY

Stability: This product is stable.

Conditions to Avoid: Heat, open flames and other ignition sources.

Incompatible Products: Avoid contact with strong acids or strong oxidizing agents.

Hazardous Decomposition: Thermal decomposition may yield carbon monoxide.

Hazardous Reactions: Product will not undergo hazardous polymerization.

SECTION XI – TOXICOLOGICAL INFORMATION

Acute Toxicity:

Dipropylene glycol momomethyl ether 34590-94-8

Acute Ingestion LD50 rat: > 5,000 mg/kg

Acute Dermal LD50 rabbit: 9,510 mg/kg

Chronic Toxicity:

No component of this product, present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen or potential carcinogen by NTP, OSHA and or IARC.

Reproductive Toxicity:

No information available.

Target Organs:

Eyes, skin

SECTION XII – Ecological Information

If this product becomes a waste, it will not exhibit the properties of ignitability, corrosivity, reactivity or environmentally persistent toxicity. The material should not be flushed into a sewer system. This product should not be released to the environment without chemical treatment.

Bio-accumulative Potential: There is no evidence to suggest bioaccumulation will occur.

Mobility: Accidental spillage may lead to penetration in the soil and groundwater. However, there is no evidence that this would cause adverse ecological effects.

SECTION XIII – DISPOSAL CONSIDERATIONS

Waste Disposal Methods: Dispose of in accordance with all applicable local, state and federal regulations. Do not discharge effluent containing this product into lakes, streams, ponds or estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your local State Water Board or Regional Office of the EPA.

SECTION XIV – TRANSPORTATION INFORMATION

The basic description below is specific to the container size. This information is provided for at a glance DOT information. Please refer to the container and/or shipping papers for the appropriate shipping description before tendering this material for shipment. Dangerous goods descriptions may not reflect end-use or region-specific exceptions that can be applied. For additional information, please contact the distributor listed in section 1 of this SDS.

No UN Packaging or Shipping Doc. Req.49 CFR 173.154

TDG: Not Regulated

DOT: Not Regulated

IATA: Not Regulated

IMDG/IM: Not Regulated

SECTION XV – REGULATORY INFORMATION

TSCA Inventory Status: All components of this material are listed on or are exempted from the US Toxic Substances Control Act (TSCA) inventory.

US Federal Regulations:

Section 313 of Title III of the Superfund Amendments and Reauthorization ACT of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372:

SARA 311/312 Hazardous Categorization

Acute Health Hazard	No
Chronic Health Hazard	No
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

TSCA 12(b) – Export Notification:

This material does not contain any components that are subject to the US Toxic Substances Control act (TSCA) section 12(b) Export Notification requirements.

Clean Air Act, Section 12 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product does not contain any reportable HAPs.

Chemical Weapons Convention (CWC):

This product does not contain any listed substances.

California Proposition 65: This product contains no listed substances known to the state of California to cause cancer, birth defects or other reproductive harm at levels which require reporting under the state statute.

SECTION XVI – OTHER INFORMATION

Prepared By: S Trujillo

Release: 09/28/16

Revision Issued: 9/24/21

Revision History: Updated address

The information herein is based on data considered to be accurate. However, no warranty is expressed or implied regarding the accuracy of these data or results. Also this shall not establish a legally valid contractual relationship.

Vendor assumes no responsibility for injury to vendee or third person proximately caused if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in use of the material.

Our products are intended for sale to industrial and commercial customers. We encourage customers to inspect and test our products before use and to satisfy themselves as to suitability for their specific applications.

Warranty: The manufacturer warrants that products sold comply with specifications as represented and will perform satisfactorily if used according to the directions, or the manufacturer will refund or replace any unused portion thereof, for a period of one year from the date of manufacture. The manufacturer does not make any other warranty, or assume responsibility of any kind, expressed or implied regarding the effect or result of the products use; and assumes no responsibility of injury to vendee or third parties proximately caused by the material if reasonable safety procedures are not adhered to.